

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2004201415 B8**

(54) Title
Thermal insulation liner

(51) International Patent Classification(s)
B65D 90/04 (2006.01) **B65D 88/74** (2006.01)

(21) Application No: **2004201415** (22) Date of Filing: **2004.04.02**

(30) Priority Data

(31) Number	(32) Date	(33) Country
PI20031276	2003.04.07	MY

(43) Publication Date: **2004.10.21**

(43) Publication Journal Date: **2004.10.21**

(44) Accepted Journal Date: **2010.12.02**

(48) Corrigenda Journal Date: **2011.04.21**

(71) Applicant(s)
San Miguel Corporation

(72) Inventor(s)
Leong, Lawrence Yong Joon

(74) Agent / Attorney
Griffith Hack, Level 3 509 St Kilda Road, Melbourne, VIC, 3004

(56) Related Art
US 5632400
US 4911317
US 5143245

ABSTRACT

THERMAL INSULATION LINER

5 There is disclosed a thermally reflective liner
(20) for providing thermal insulation within a container
(1). The liner (20) comprises: four long panels (25)
which are joined along their long sides forming a tube of
approximately rectangular cross section; an end panel (30)
10 which seals the end of the tube; means for closing the tube
(35; 60), such that total thermal insulation can be
provided to the enclosed space within the liner (20); a
plurality of loops (40) provided along the long seams (45)
of the liner (20); and at least one piece of webbing
15 material (50) which can be threaded between the plurality
of loops (40) on the liner (20) and a plurality of hooks
(15) on the container (1) to retain the liner (20) within
the container (1), such that an air gap is provided
between the sides and top of the liner (20) and the
20 container (1).

A method for thermally insulating a container (1)
with a thermally reflective liner (20) is also disclosed.

Fig. 2

25




Fig. 1




Fig. 2




Fig. 3

AUSTRALIA
Patents Act 1990

COMPLETE SPECIFICATION
STANDARD PATENT

Applicant:

HONG LEONG INDUSTRIES BERHAD

Invention Title:

THERMAL INSULATION LINER

The following statement is a full description of this invention, including the best method of performing it known to me/us:

TITLE

THERMAL INSULATION LINERFIELD OF THE INVENTION

5

The present invention relates to the protection of goods and products against either elevated or decreased temperature with respect to ambient temperature, during shipping or transportation in sea-freight shipping
10 containers.

BACKGROUND TO THE INVENTION

Within sea-freight containers there is often a
15 temperature difference of about 10°C to 15°C with respect to the ambient temperature. Both the internal temperature within the container, and the ambient temperature, can rise quickly. Such temperature fluctuations can cause damage to the container contents, especially to perishable
20 goods.

To prevent damage to the container contents, thermal insulation is required which slows the rate of change of the temperature within the container. Thick
25 blankets of wool or similar material and plastic bubble material can be used to provide thermal insulation.

A sleeve like liner can be used as a thermal insulator which is inflated using a motorised fan or
30 blower. Such an inflatable liner has the disadvantage that it can only be readily used where electric power is available.

Some liners are used where the walls of the liner
35 are adhered to the walls of the container using double-sided tape, or hook-and-loop material. The effectiveness of such liners is reduced by the direct contact of the

liner with the wall of the container. Owing to the direct contact between the liner and the container walls, heat is conducted from the walls to the insulation materials. U.S. Patent number 5,638,979 discloses a bubble foil with a reflective surface. These types of bubble foil are bulky and heavy and cannot be effectively used in sea-freight containers.

All the above mentioned thermal insulation devices require a substantial amount of time for the installation of the insulator.

Thus, an object of the invention is to provide a thermal insulation device for use in sea-freight shipping containers, having improved thermal insulation properties, and being easier to install.

SUMMARY OF THE INVENTION

In accordance with one aspect of the present invention there is provided a thermally reflective liner for providing thermal insulation within a shipping container, the liner comprising:

at least three long panels which are joined along their long sides forming a part tube or tube;

an end panel which seals the end of the part tube or tube;

means for closing the front end of the part tube or tube, such that thermal insulation can be provided to the space within the liner; and

a plurality of first attachments provided along the upper joined long sides of the liner;

wherein at least one piece of webbing material can be held between the plurality of first attachments on the liner and a plurality of second attachments on the

shipping container to retain the liner within the shipping container, such that the liner hangs within the shipping container, and provides an air gap between the sides and top of the liner and the shipping container.

5

In accordance with another aspect of the present invention there is provided a method for thermally insulating a shipping container with a thermally reflective liner, the liner comprising:

10

at least three long panels which are joined along their long sides forming a part tube or tube of approximately rectangular cross section;

15

an end panel which seals the end of the part tube or tube;

means for closing the front end of the part tube or tube, such that thermal insulation can be provided to the space within the liner; and

20

a plurality of loops provided along the upper joined long sides of the liner;

the method comprising the steps of:

positioning the end panel of the liner at the rear end of the empty shipping container;

25

attaching pieces of webbing material to the corners at the rear end of the shipping container;

30

feeding each piece of webbing material through the plurality of loops and through hooks on the shipping container such that the liner hangs within the shipping container, and provides an air gap between the sides and top of the liner and the shipping container;

loading the shipping container; and

closing the liner to enclose the contents of the shipping container.

In accordance with yet another aspect of the present invention there is provided a method for thermally insulating a shipping container with a thermally reflective liner, the liner comprising:

at least three long panels which are joined along their long sides forming a part tube or tube of approximately rectangular cross section;

an end panel which seals the end of the part tube or tube;

means for closing the front end of the part tube or tube, such that thermal insulation can be provided to the space within the liner; and

a plurality of eyelets provided along the upper joined long sides of the liner;

the method comprising the steps of:
positioning the end panel of the liner at the rear end of the empty shipping container;

hooking a connecting hook between each eyelet and a corresponding portion of webbing material that is threaded through shipping container hooks on the shipping container such that the liner hangs within the shipping container, and provides an air gap between the sides and top of the liner and the shipping container;

loading the shipping container; and
closing the liner to enclose the contents of the shipping container.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the present invention can be more readily understood, an embodiment will now be described, by way of example only, with reference to the accompanying

drawings, in which:

Figure 1: is a cross section of one embodiment of a liner, inserted into a sea-freight shipping container;

5 Figure 2: is a top view of the liner and container of figure 1;

Figure 3: is a perspective view of the liner of figure 1;

10 Figure 4: is a top view of another embodiment of a liner; and

Figure 5: is a perspective view of yet another embodiment of a liner.

DETAILED DESCRIPTION

15

Figures 1 to 3 show a first embodiment of a liner 20 which can be installed in a container 1. The liner 20 is in the shape of a sleeve, with dimensions which

substantially correspond to that of the container 1 into which the liner 20 is to be inserted.

5 The liner 20 has four long panels 25 which are each joined along the longest sides to the adjacent long panels 25, forming long seams 26. Thus, the liner 20 has an approximately rectangular cross section.

10 An end panel 30 seals an end of the liner 20. Four sealable panels 35 of rectangular cross section are each joined, along a long side, to the short sides of the liner 20. Thus, a sealable opening is formed in the liner 20.

15 Loops 40 are provided along the seams 45 of the liner 20. Hooks 15 are positioned along the vertices 18 of the container 1.

20 To insert the liner 20 into a container 1, the end panel 30 is first positioned at the back end 5 of the container 1. Four pieces of webbing material, such as cords 50, are used to retain the liner 20 in position inside the container 1. A knot is made at the end of each of the cords 50, tying the cords 50 to rear tying points 6
25 at each corner on the back end 5 of the container 1.

30 Each cord 50 is then fed alternately through the loops 40 on the liner 20 and the corresponding hooks 15 on the container 1. Once the cord 50 has been fed through to the front 7 of the container 1, knots 55 are tied at the end of each cord 50, attaching the cords 50 to front tying points 11. Thus, the liner 20 is inserted into the container 1.

35 Once the container 1 has been loaded, the four sealable panels 35 can be closed to provide a thermal seal which completely surrounds the contents of the container

1. The sealable panels 35 are provided with a ties 60 to securely close the liner 20.

Figure 4 illustrates another embodiment of the
5 liner having different retaining means to retain the liner
20 in the container 1. As in the previous embodiment the
container may still be provided with hooks 15 at the
vertices 18 of the container 1. The loops 40 in this
10 embodiment are not as wide as the loops of the previous
embodiment but are shaped more as eyelets. The eyelets
may be flexible, that is, made of a woven fabric, or
stiffer where they are made of a metal or plastics. Metal
connecting hooks 71 may be either permanently attached to
15 eyelets 40 or can be un-hooked therefrom. Metal hooks 71
are designed to hook onto web 50 catching the lengths of
web 50 between container hooks 15.

In this way, web 50 does not need to be
constantly threaded and unthreaded from container hooks 15
20 and liner loops 40. Rather, the web may remain tied to
the container at front and rear tying points 11 and 6
respectively and threaded through hooks 15. Once the
liner 20 is inserted into the container 1, the metal
connecting hooks 71 are hooked onto the adjacent web 50
25 threaded through the container hooks 15. This allows for
a much simpler and faster attachment process, particularly
for inserting the liner into a container.

Of course, the arrangement of the metal
30 connecting hooks 71 and threaded web may be reversed such
that the web is permanently held in place threaded through
loops 40 on the liner and the removable connecting hooks
71 are located on container hooks 15. Connecting hooks 71
may be detachable from eyelets 40 or container hooks 15,
35 or they may be permanently connected to either the eyelets
40 or container hooks 15 such that connecting hooks 17 are
not misplaced.

Other suitable means for attaching the liner to the container interior may also be used. For example, in place of connecting hooks 71 the liner or container may include velcro loops that loop around web 50 and fold over to attach with itself and form a velcro loop.

Another embodiment of the liner is illustrated in figure 5. In this embodiment the bottom panel is missing such that there are only three long panels 25, an end panel 30 and only three sealable panels 35. The resulting shape is a part tube with one panel missing. This embodiment is brought about because it is not always necessary or desirable to have a bottom panel lining the base of the container.

Liner loops 40 are still provided in this embodiment along the lower edge 72 of the side panels. This maintains the side panels firmly aligned with the side walls of the container.

It is understood that some containers may be of irregular geometry, for example having more than four sides, such as five, and in these cases a liner may be purpose made for such containers along the lines of the above concept.

Such custom made liners may comprise more than four panels, such as five or six, forming a tube or part tube.

To ensure that the liner 20 does not droop over the front end 10 of the container 1, additional cord 65 is provided to retain the seam 70 (located between the uppermost long panel 25 and the uppermost sealable panel 35) to the container 1.

The liner 20 is made of a reinforced material such as a woven fabric, and further laminated with a thermally reflective material. Such thermally reflective materials include aluminium and/or vapourised aluminium sheet.

5

The liner 20 is light weight and tough. The liner 20 must be able to withstand the rough treatment of the forklifts and pallet jacks used to load/unload goods from the container 1 is an important characteristic of the liner 20. The woven fabric provides the durability required of the liner 20, while the aluminium provides the thermal reflective surface.

10

When the liner 20 is inserted as described above, the liner 20 is positioned within the container 1 such that an air gap is formed on the long sides and top between the liner 20 and the container 1.

15

The thermally reflective surface of the liner 20 reduces heat transfer by thermal radiation to (or from) the air immediately adjacent to the liner 20. The air gap between the container 1 and the liner 20 improves the thermal insulation by minimising conduction from the liner 20 to the container 1.

20

It will be understood to persons skilled in the art of the invention that many modifications may be made without departing from the scope of the invention.

25

In the claims which follow and in the preceding description of the invention, except where the context requires otherwise due to express language or necessary implication, the word "comprise" or variations such as "comprises" or "comprising" is used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

30

35

It is to be understood that, if any prior art publication is referred to herein, such reference does not constitute an admission that the publication forms a part of the common general knowledge in the art, in Australia or any other country.

40

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A thermally reflective liner for providing thermal insulation within a shipping container , the liner
5 comprising:

at least three long panels which are joined along their long sides forming a part tube or tube;

an end panel which seals the end of the part tube or tube;

10 means for closing the front end of the part tube or tube, such that thermal insulation can be provided to the space within the liner; and

a plurality of first attachments provided along the upper joined long sides of the liner ;

15 wherein at least one piece of webbing material can be held between the plurality of first attachments on the liner and a plurality of second attachments on the shipping container to retain the liner within the shipping container, such that the liner hangs within the shipping
20 container, and provides an air gap between the sides and top of the liner and the shipping container.

2. The liner as claimed in claim 1, further wherein the liner comprises three long panels which are joined
25 along their long sides forming a part tube of approximately rectangular cross section.

3. The liner as claimed in claim 1, wherein the liner comprises four long panels which are joined along
30 their long sides forming a tube of approximately rectangular cross section and wherein total thermal insulation can be provided to the enclosed space within the liner.

4. The liner as claimed in any one of the preceding claims, wherein the first attachments are loops provided on seams of the joined long sides of the liner, and the
5 second attachments are hooks on the shipping container, wherein the webbing material is threaded between the loops on the liner and the hooks on the shipping container.

5. The liner as claimed in any one of claims 1 to 3,
10 wherein the first attachments are eyelets provided along seams on the joined long sides of the liner and the second attachments are hooks on the shipping container, wherein the webbing material is threaded through one of the plurality of eyelets or hooks and a connecting hook is
15 attached to the other of the eyelets or hooks at one end while the other end holds the webbing material.

6. The liner as claimed in claim 5, further wherein the connecting hooks are permanently attached to each one
20 of the plurality of eyelets or shipping container hooks.

7. The liner as claimed in claim 1, further wherein a plurality of loops are provided along a short side of the uppermost long panel such that a further piece of
25 webbing material can be threaded between the plurality of loops on the liner and a plurality of hooks on uppermost opening of the shipping container.

8. The liner as claimed in claim 1, further wherein
30 the means for closing the front end of the tube or part tube is a plurality of panels of the thermally reflective material which may be overlapped to close the liner.

9. The liner as claimed in any one of the preceding claims, wherein the liner material is light weight and tough.

5 10. The liner as claimed in claim 9, wherein the liner is made of a flexible, reinforced material, laminated with a thermally reflective material.

11. A method for thermally insulating a shipping
10 container with a thermally reflective liner, the liner comprising:

at least three long panels which are joined along their long sides forming a part tube or tube of approximately rectangular cross section;

15 an end panel which seals the end of the part tube or tube;

means for closing the front end of the part tube or tube, such that thermal insulation can be provided to the space within the liner; and

20 a plurality of loops provided along the upper joined long sides of the liner;

the method comprising the steps of:

positioning the end panel of the liner at the rear end of the empty shipping container;

25 attaching pieces of webbing material to the corners at the rear end of the shipping container;

feeding each piece of webbing material through the plurality of loops and through hooks on the shipping container such that the liner hangs within the shipping
30 container, and provides an air gap between the sides and top of the liner and the shipping container;

loading the shipping container; and

closing the liner to enclose the contents of the shipping container.

12. A method for thermally insulating a shipping container with a thermally reflective liner, the liner comprising:

at least three long panels which are joined along their long sides forming a part tube or tube of approximately rectangular cross section;

an end panel which seals the end of the part tube or tube;

means for closing the front end of the part tube or tube, such that thermal insulation can be provided to the space within the liner; and

a plurality of eyelets provided along the upper joined long sides of the liner;

the method comprising the steps of:
positioning the end panel of the liner at the rear end of the empty shipping container;

hooking a connecting hook between each eyelet and a corresponding portion of webbing material that is threaded through shipping container hooks on the shipping container such that the liner hangs within the shipping container, and provides an air gap between the sides and top of the liner and the shipping container;

loading the shipping container; and
closing the liner to enclose the contents of the shipping container.

13. A thermally reflective liner for providing thermal insulation within a shipping container substantially as herein described with reference to the accompanying drawings.

2004201415 08 Oct 2010

- 14 -

14. A method for thermally insulating a shipping container with a thermally reflective liner substantially as herein described with reference to the accompanying
5 drawings.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5